

Product Specification Sheet



Model No.	Description	Length	Depth	Height	Voltage	Amps	Power Cord	Est. Ship Weight
CHS40E-4	3 Wells	52.5"	39"	53"	115	3.8/11.6	NO	490
CHS40E-6	4 Wells	76.5"	39"	53"	115	5/17.6	NO	690
CHS40E-8	6 Wells	100.5"	39"	53"	115	7.5/23.1	NO	943

MODEL NUMBER SUFFIX - B = Black S = Stainless Steel

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice

Standard Features and Options

CONSTRUCTION

- Foamed in place CFC free foam
- Single pane tempered front safety glass
- Heavy gauge steel super structure
- ETL listed for safety and sanitation
- New extruded doors and door tracks

INTERIOR

- Stainless steel ends
- Stainless steel deck area around wells (for easy cleaning)
- 12x20 Wet or dry heated individual wells
- Individual thermostatically controlled wells
- Separate drain for each well
- Coated heat lamp over each well

EXTERIOR

- Front and ends, white, stainless steel, or black
- Stainless Steel exterior rear
- Stainless steel mirror trim
- Double pane rear removable doors
- Stainless steel heavy gauge top - 17" W
- Vented front minimizes moisture on glass
- 1" bumper

THIS HOT CASE IS MADE TO MATCH THE 40E SERIES SERVICE CASES

Important Note:

Due to safety concerns - the end panels can not be removed nor can this be connected to any other 40E Series unit.

Electrical Requirements

Model No.	Wells	Volts	Phase	AMPS
CHS40E-4	3	120V/208V	1	4.4A/17.3A
		120V/240V	1	4.4A/20.0A
		120V/208V	3	4.4A/10.0A
		120V/240V	3	4.4A/11.6A
CHS40E-6	4	120V/208V	1	5.0A/21.1A
		120V/240V	1	5.0A/26.7A
		120V/208V	3	5.0A/15.3A
		120V/240V	3	5.0A/17.6A
CHS40E-8	6	120V/208V	1	7.5A/34.6A
		120V/240V	1	7.5A/40.0A
		120V/208V	3	7.5A/20.0A
		120V/240V	3	8.7A/23.1A

Technical Data



Model No.	CHS40E-4	CHS40E-6	CHS40E-8
Length	52.5"	76.5"	100.5"
Height	53"	53"	53"
Depth	39"	39"	39"
# of wells	3	4	6
(Dimensions are +/- 1/4")			
Voltage - standard	120/240	120/240	120/240
Phase	3	3	3
Amperage	4.4/11.6	5.0/17.6	8.7/23.1
Voltage - optional	120/240	120/240	120/240
Phase	1	1	1
Amperage	4.4/20.00	5/21.1	7.5/34.6
Voltage - optional	120/208	120/208	120/208
Phase	3	3	3
Amperage	4.4/10	5/15.3	7.5/20
Voltage - optional	120/208	120/208	120/208
Phase	1	1	1
Amperage	4.4/17.3	5/21.1	7.5/34.6
Exterior color	W, B, S	W, B, S	W, B, S
Interior color	S	S	S
Floors	S	S	S
# of top rear doors	2	2	2
Front viewing area	19.9"	19.9"	19.9"
Bottom Storage	NO	NO	NO
Door size	(2) 20.5" x 23.5"	(2) 31" x 32.62"	(4) 20.5" x 23.5"
Shipping Info			
Height	58"	58"	58"
Depth	45"	45"	45"
Length	61"	87"	109"
Gross weight	490	690	943
Cubic feet	90	128	164

Suffix

B = Black
S = Stainless Steel

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Cases are equipped with drains; check your local building codes for connection requirements.
- Specification subject to change without notice

Technical Data • Side View • Plan View





CHS40E-6

6" ELECTRICAL INFO

208/120V SINGLE PHASE 21.1/5.0 AMPS 30/15 FUSE
240/120V SINGLE PHASE 26.7/5.0 AMPS 35/15 FUSE

208/120V 3PHASE 15.3/5.0 AMPS 20/15 FUSE
240/120 3PHASE 17.6/5.0 AMPS 25/15 FUSE





CHS40E-4

4" ELECTRICAL INFO

208/120V SINGLE PHASE 17.3/4.4 AMPS 25/15 FUSE
240/120V SINGLE PHASE 20.0/4.4 AMPS 25/15 FUSE

208/120V 3PHASE 10.0/4.4 AMPS 15/15 FUSE
240/120 3PHASE 11.6/4.4 AMPS 15/15 FUSE



CHS40E-8

8" ELECTRICAL INFO

208/120V SINGLE PHASE 34.6/7.5 AMPS 40/15 FUSE
240/120V SINGLE PHASE 40.0/7.5 AMPS 50/15 FUSE

208/120V 3PHASE 20.0/7.5 AMPS 25/15 FUSE
240/120 3PHASE 23.1/8.7 AMPS 30/15 FUSE

