# Howard McCray Open Merchandisers 32 Series Endless Design Cooler From Bush Refrigeration

# Open Merchandisers-32 Series Endless Design - Produce Case with Shelf

PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

SC-P32E-4S R-P32E-4S	SC-P32E-6S R-P32E-6S	SC-P32E-8S R-P32E-8S	
50"	74"	98"	
48"	72"	96"	
72-3/4"	72-3/4"	72-3/4"	
71-7/8"	71-7/8"	71-7/8"	
29-3/8"	29-3/8"	29-3/8"	
	50" 48" 72-3/4" 71-7/8"	R-P32E-4S R-P32E-6S  50" 74" 48" 72" 72-3/4" 72-3/4" 71-7/8" 71-7/8"	

• Specification subject to change without notice

## Howard McCray Open Merchandisers 32 Series Endless Design Cooler From Bush Refrigeration

Open Merchandisers 32 Series – Endless Design - Produce Case with Shelf

## **Standard Specifications and Optional Features**

Construction UL Classified to ANSI/NSF 7 Heavy gauge steel super structure Foamed in place CFC free foam Multi deck Endless design allows for continuous line up	Finishes  Designer white or black end panels Designer white or black front rail Designer white or black front color band Designer white or black end trim Coated galvanized rear
Interior  Designer white or black end panels Removable designer white or black floor pans Designer white or black perforated rear wall (for even air distribution) Full length lighting at top of unit 1 level of 14" shelving with product stop Telescoping display rack 2 levels of product display Over 50" of display area 14" Full length mirror to enhance product display Stylish tag molding on each shelf	Refrigeration R404A expansion valve system Low velocity fans located below deck area (to insure even flow of air) Pressure control maintains constant temperatures Automatic defrost controlled by time clock (self contained units only) Air screen technology Self contained system Copeland hermetic unit Remotes available
Exterior  Designer white or black ends and front Designer white or black color-band Designer white or black end trim Removable front grille allows for cleaning and servicing 1" designer gray bumper	<b>Lighting</b> 1 row at inside top of unit
ELECTRICAL REQUIREMENTS Unit must be hard wired UL/CUL listed See Tech page for details on voltage	Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.  Important Note: Product must be cooled before being displayed within the case.  Important Note: DRAIN IS REQUIRED

#### **OPTIONAL FEATURES**

4" of Plexiglas on end panel
Stainless steel, laminated or paint
Security cover
Plexiglas divider for line ups
Digital thermometer

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)





## Howard McCray Open Merchandisers 32 Series Endless Design Cooler From Bush Refrigeration

## Open Merchandisers 32 Series – Endless Design - Produce Case with Shelf

### **Technical Data**

Model #	Self Contained	SC-P32E-4S	SC-P32E-6S	SC-P32E-8S
	Remote	R-P32E-4S	R-P32E-6S	R-P32E-8S
Length with ends Length without ends Height with ends Height without ends Depth with ends (Dimensions are +/- 1/4")		50" 48" 72-3/8" 71-7/8" 29-3/8"	74" 72" 72-3/8" 71-7/8" 29-3/8"	98" 96" 72-3/8" 71-7/8" 29-3/8"
Operating temperature Refrigerant (expansion valve) Compressor size HP Pressure control settings @ 75°F, 55%RH  Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage Cord and plug	Self contained  CUT IN  CUT OUT		38°F to 41°F R404A 3/4 88 54 3 @ 30 min. 6000 115/208-230V 12.0A 3.2A L14-20P	38°F to 41°F R404A 1 88 54 3 @ 30 min. 8000 115/208-230V 13.8A 3.8A L14-20P
Exterior color Interior color Inside end panels Floors		White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

#### SHIPPING INFORMATION

Height	Self contained	76"	76"	76"
Depth		44"	44"	44"
Length		61"	87"	109"
Gross weight		615#	825#	1097#
Cubic feet	Remote	490#   118ft <sup>3</sup>	675# 168ft³	922# 211ft³

- · Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- · Cases are equipped with drains; check your local building codes for connection requirements.
- · Specification subject to change without notice