



Glass Door Counter Tops



VR-7-HC

(FORMALLY JUNIOR-1-US)

Height..... 53.75"
Length..... 21.00"
Depth..... 23.63"
Cubic Ft. 7
Liters 198
Bottles (20oz) ... 90
Cans (12oz) 216



VR-8-HC

(FORMALLY V-252-US)

Height..... 59.13"
Length..... 21.00"
Depth..... 23.63"
Cubic Ft. 8
Liters 227
Bottles (20oz) ... 120
Cans (12oz) 252



VR-10-HC

Height..... 54.00"
Length..... 25.63"
Depth..... 22.75"
Cubic Ft. 10
Liters 283
Bottles (20oz) ... 126
Cans (12oz) 288



Features

- Interior and exterior constructed of heavy duty white coated steel
- Polyurethane insulation with cyclopentane as blowing agent
- Double pane glass door with Low-E protection
- Illuminated top header sign (VR-8-US)
- Externally mounted hinged glass doors
- Recessed door handle
- Heavy duty shelves with clips
- Heavy duty hinges with self closing mechanism
- Forced air evaporator for rapid temperature "Pull Down"
- Self contained heavy duty 134a condensing unit
- Energy efficient LED lighting
- UL Classified to ANSI/NSF 7



VR-12-HC

Height..... 54.00"
Length..... 25.63"
Depth..... 22.75"
Cubic Ft. 10
Liters 340
Bottles (20oz) ... 168
Cans (12oz) 384



VR-15-HC

Height..... 64.75"
Length..... 30.00"
Depth..... 25.75"
Cubic Ft. 15
Liters 425
Bottles (20oz) ... 192
Cans (12oz) 504

Model No.	Description	Voltage	Amps	Temp	HP	Est. Ship Weight
VR-7-HC	1 Door/2 Shelves	115	3.7	32°F - 39°F	1/5	187#
VR-8-HC	1 Door/3 Shelves	115	3.8	32°F - 39°F	1/5	205#
VR-10-HC	1 Door/3 Shelves	115	3.7	32°F - 39°F	1/5	230#
VR-12-HC	1 Door/3 Shelves	115	4.5	32°F - 39°F	1/5	235#
VR-15-HC	1 Door/3 Shelves	115	3.7	32°F - 39°F	1/4	310#



Technical Data / Glass Door

Model #	VR-7-HC	VR-8-HC	VR-10-HC	VR-12-HC	V-15-HC
Outside Dimensions					
Depth	23.63"	23.63"	22.75"	22.75"	25.75"
Length	21.00"	21.00"	25.63"	25.63"	30.00"
Height	53.75"	59.13"	54.00"	62.00"	64.75"
Door Size	21.75" x 42.25"	20.63" x 38.50"	26.25" x 43.00"	26.25" x 50.3"	30.00" x 47.75"
Door Type	1 swing	1 swing	1 swing	1 swing	1 swing
Inside Dimensions					
Depth	18"	18"	19.00"	19.00"	21.75"
Length	17.50"	17.50"	22.00"	22.00"	25.25"
Height	38.75"	44.63"	39.50"	47.50"	45.88"
Shelf Size	16.75"x16.75"	16.75"x16.75"	21.25"x17.50"	21.25"x17.50"	24.50"x19.50"
# of Shelves	2	3	3	3	3
Capacity: Cubic Foot	7	8	10	12	15
Specifications					
Operating Temperature	32°F-39°F	32°F-39°F	32°F-39°F	32°F-39°F	32°F-39°F
Refrigerant	134a	134a	134a	134a	134a
Compressor Size HP	1/5	1/5	1/5	1/5	1/4
Voltage	115	115	115	115	115
Amperage	3.7	3.8	3.7	4.5	3.7
Cord and Plug	yes	yes	yes	yes	yes
Shipping Dimensions					
Depth	28.00"	28.00"	28.00"	28.00"	30.00"
Length	25.00"	25.00"	30.00"	30.00"	33"
Height	60.00"	66.0"	60.00"	66.00"	68.00"
Gross Weight lbs.	187	205	230	235	310
Cubic feet	24	26	29	32	35

- Cases are designed to operate at 75°F and 55% relative humidity.
- Specification subject to change without notice.

